

FLAGON

TPO METAL SHEET

TECHNICAL DATA SHEET

ANZ-TDS-130-FLAGON TPO METAL SHEET



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

DESCRIPTION

FLAGON TPO METAL SHEET is made of a flexible modified polyolefin FLAGON TPO membrane bonded to a galvanised steel sheet. FLAGON TPO METAL SHEET is used for the realisation of custom made finishing elements of a roof such as flashings and profiles. It is distinguished by a high resistance to weathering and UV-rays.

FLAGON TPO METAL SHEET is compatible with FLAGON TPO membranes and ALSAN EP M.

APPLICATION

- Used for custom made finishing elements of a roof in combination with the flexible TPO waterproofing systems.
- Weld the FLAGON TPO membrane onto FLAGON TPO METAL SHEET with hot air.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

SPECIFICATIONS	FLAGON TPO METAL SHEET
Upper side	Flexible TPO
Lower side	Galvanised steel
Total thickness	1,8 mm
Thickness PVC membrane	1,2 mm
Thickness steel sheet	0,6 mm
Width	1,00 m
Length	2 m / 3 m
Mass	5,5 kg/m ²

STORAGE AND HANDLING

If stored outdoors, cover with an opaque protection cover after removal of the delivery packaging.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative and/or the contractor are responsible for checking the suitability of products for their intended use.



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_FLAGON_TPO_METAL_SHEET_2024_RA

1/1