

ALSAN VOILE FLASHING

TECHNICAL DATA SHEET

ANZ-TDS-132-ALSAN VOILE FLASHING



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

FOUNDATIONS

GREEN ROOFS

DESCRIPTION

ALSAN VOILE FLASHING is used as reinforcement and ensures that a minimum layer thickness of the ALSAN FLASHING JARDIN waterproofing resin must be applied.



APPLICATION

- Apply the ALSAN VOILE FLASHING on top of the first layer of wet resin in place, then install the last second layer of the resin directly on top.
- The ALSAN VOILE FLASHING overlap must be at least 50 mm. Resin must be applied between the overlaps.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING & PROPERTIES

SPECIFICATIONS	TEST METHOD	ALSAN VOILE FLASHING
Density	-	110 g/m ²
Thickness	-	0,37 mm
Colour	-	White
Width	-	100 / 150 / 200 / 260 / 350mm
Length	-	50 m

STORAGE AND HANDLING

Store in a dry place protected from moisture and pollution.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative and/or the contractor are responsible for checking the suitability of products for their intended use.



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_ALSAN_VOILE_FLASHING_2024_RA

1/1